

DESCRIPTION

The MT3503/MT3503A is a high efficiency, 3.5A current mode synchronous step-down DC/DC converter with a wide input voltage range from 4.5V to 18V. The device integrates lower high side and low side MOSFETs to achieve high efficiency conversion. The current mode control architecture supports fast transient response and internal compensation. The MT3503/MT3503A provides complete fault protection such as input under-voltage lockout, output short circuit protection, over current protection, and thermal shutdown. The switching frequency is internally set at 1MHz. MT3503 and MT3503A have different operation modes:

- MT3503 is automatic PSM/PWM mode.
- MT3503A is Forced PWM mode.

To improve the light load efficiency, MT3503 has the light load power saving mode (PSM) to minimize the switching loss by reducing the switching frequency. The MT3503/MT3503A is available in the TSOT23_6L package.

FEATURES

- Input Voltage Range from 4.5V to 18V
- +/- 2% 0.6V Feedback Voltage Accuracy
- Adjustable Output Voltage from 0.6V to 12V
- 1MHz Switching Frequency
- Built-in 70mΩ/30mΩ Power Switch
- Continuous Output Current up to 3.5A
- High Efficiency up to 94%
- Internal Soft-Start
- Input Under Voltage Lockout (UVLO)
- Cycle-by-Cycle Current Limit Protection
- Over-Load and Short Circuit Protection
- Thermal Shutdown Protection
- Available in a Small TSOT23_6L Package
- Pb-Free RoHS Compliant

APPLICATIONS

- Wireless and DSL Card
- Portable/Handheld Device
- STB, TV, Sound Bar, MP3 Player
- Slim DVD, SSD
- Microprocessor and DSP Core Supply

Typical Applications

